


SEW SPECIFICATION OF SCL-2-400-H (CRANKLESS DRIVE)		
DESCRIPTION	UNIT	
CAPACITY	T	400
RATING POINT	mm	13
NUMBER OF SUSPENSION	—	2
STROKE LENGTH	mm	600
CONTINUOUS SPEED (VARIABLE)	spm	10-20
MAX DIE HEIGHT (SDAU)	mm	850
SLIDE ADJUSTMENT (MOTORIZED)	mm	300
BOLSTER AREA (LRXFB)	mm	2800x1600
SLIDE AREA (LRXFB)	mm	2800x1600
SLIDE GUIDING	—	8
MAIN MOTOR	kW	45
FLOOR TO TOP OF BOLSTER	mm	600
PRESS ACCORDING ACCURACY	—	JIS 6402-1985 GRADE-1
DRIVE	—	ECCENTRIC GEAR
LUBRICATION	—	CENTRALIZED RECIRCULATING OIL
BOLSTER THICKNESS	mm	215

DIE CUSHION (OPTIONAL)

CAPACITY	tone	60
STROKE	mm	160
PAD AREA	mm	2350x1150

REV. NO.	ALTERATION	DATE	DRAWN BY



TITLE
G.A.DRAWING

DRG. NO. SCL-2-400-H-08
REV. 00



DRAWN BY PRITESH
CHECKED BY
APPROVED BY VR
DATE 12/01/2020