


SEW SPECIFICATION OF SCL-2-400-H (CRANKLESS DRIVE)		
DESCRIPTION	UNIT	
CAPACITY	T	400
RATING POINT	mm	13
NUMBER OF SUSPENSION	—	2
STROKE LENGTH	mm	600
CONTINUOUS SPEED (VARIABLE)	spm	10-20
MAX DIE HEIGHT (SDAU)	mm	850
SLIDE ADJUSTMENT (MOTORIZED)	mm	300
BOLSTER AREA (LRXFB)	mm	3100x1600
SLIDE AREA (LRXFB)	mm	3100x1600
SLIDE GUIDING	—	8
MAIN MOTOR	kW	45
FLOOR TO TOP OF BOLSTER	mm	600
PRESS ACCORDING ACCURACY	—	JIS 6402-1985 GRADE-1
DRIVE	—	ECCENTRIC GEAR
LUBRICATION	—	CENTRALIZED RECIRCULATING OIL
BOLSTER THICKNESS	mm	215

DIE CUSHION (OPTIONAL)		
DESCRIPTION	UNIT	
CAPACITY	tone	60
STROKE	mm	160
PAD AREA	mm	2650X1150

SEW SINGHAL POWER PRESSES PVT.LTD	
DRAWN BY	PRITESH
CHECKED BY	
APPROVED BY	VR
DATE	12/01/2020

REV. NO.	ALTERATION	DATE	DRAWN BY



TITLE	G.A.DRAWING	DRG. NO.	REV.
		SCL-2-400-H-08	00