

8-POINT GIB

**SEW SPECIFICATION OF SCL-2-800-H (CRANKLESS DRIVE)**


DESCRIPTION	UNIT	
CAPACITY	T	800
RATING POINT	mm	13
NUMBER OF SUSPENSION	—	2
STROKE LENGTH	mm	600
CONTINUOUS SPEED (VARIABLE)	spm	10-20
MAX DIE HEIGHT (SDAU)	mm	1100
SLIDE ADJUSTMENT (MOTORIZED)	mm	400
BOLSTER AREA (LRXFB)	mm	3100x1600
SLIDE AREA (LRXFB)	mm	3100x1600
SLIDE GUIDING	—	8
MAIN MOTOR	kW	90
FLOOR TO TOP OF BOLSTER	mm	600
PRESS ACCORDING ACCURACY	—	JIS 6402-1985 GRADE-1
DRIVE	—	ECCENTRIC GEAR
LUBRICATION	—	CENTRALIZED RECIRCULATING OIL
BOLSTER THICKNESS	mm	275

**DIE CUSHION (OPTIONAL)**

CAPACITY	tone	120
STROKE	mm	220
PAD AREA	mm	2650X1150



DRAWN BY	PRITESH
CHECKED BY	
APPROVED BY	VR
DATE	13/01/2020



TITLE	G.A.DRAWING	DRG. NO.	SCL-2-800-H-08	REV.	00
-------	-------------	----------	----------------	------	----