



SEW SPECIFICATION OF SNX-160 TONNE [GEARED]

PRESS CAPACITY IN TONNE	160 Tonne
STROKE LENGTH [FIX]	200 mm
TONNAGE RATING POINT [B.D.C.]	6 mm
SLIDE ADJUSTMENT	120 mm[MOTORISED]
SLIDE AREA [LxH]	720x580 mm
DIE HEIGHT [SDAU]	450 mm
BOLSTER AREA [LxH]	1250x760 mm
BOLSTER THICKNESS	160 mm
THROAT DEPTH	400 mm
CLEAR DIST. BETWEEN UPRIGHTS	760 mm
MAIN MOTOR [HP x RPM]	15x4P
MACHINE SPM.	40
FLOOR TO TOP OF BOLSTER	900 mm
OVER LOAD SAFETY	HYD. OVER LOAD
LUBRICATION	GREASE LUB.
CAM LIMIT SWITCH	ENCODER BASE E-CAMS

VARIABLE	
MACHINE SPM.	30~50
MAIN MOTOR [HP x RPM]	20X4P
DIE CUSHION (OPTIONAL)	
PNEUMATIC DIE CUSHION	10 Tonne.
DIE CUSHION STK. LENGTH	100
DIE CUSHION PAD AREA	540x340 mm

REV.	DESCRIPTION	SIGN.	DATE	NAME	SCALE	N.T.S.	DATE	DRAWN	CHECKD.	APPRD.	NAME	SCALE	N.T.S.	DATE	DRAWN	CHECKD.	APPRD.	NAME	

SEW SINGHAL POWER PRESSERS PVT.LTD

G.A. DRAWING

DRAWING: SNX-160-SC-FS-08